VOLKSWAGEN (VW) (EU) VENTO VENTO 1.8



(1992-1998)

ENGINE AAM, ABS, ADZ Capacity: 3,8 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Specialsynth MSP 5W-40	Emperol 5W-40

Change every 15000 km/ 12 months

DIFFERENTIAL FROM AUTOMATIC 01M Capacity: 0,75 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Check every 60000 km			

TRANSAXLE AUTOMATIC 01M 4. Capacity: 5,3 liter	/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		
Charles average 20000 lens / 12 magniths	-1		

Check every 30000 km/ 12 months, change every 60000 km

TRANSAXLE MANUAL 5/1 Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
Check every 12 months/ 30000 km	<u> </u>

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 24 months		

VOLKSWAGEN (VW) (EU) VENTO VENTO 1.8



(1992-1998)

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM AS OF PRODUCTION DATE 10-1996 Capacity: 5,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 12	Coolant SP 12 EVO		

COOLING SYSTEM UP TO PRODUCTION DATE 10-1996 Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Change every 24 months	1	•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.