## VOLKSWAGEN (VW) (EU) BEETLE 5C BEETLE 1.6 TDI (77 KW) (2011-2014)



<b>ENGINE</b> CAYC Capacity: 4,3 liter (Service fill)	
USE	CLIMATE
Extended drain (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 30000 km/24 months	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months	

TRANSAXLE MANUAL 0A4 5/1 Capacity: 1,8-2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 48 months/ 60000 km	,	'

TRANSAXLE SEMI-AUTOMATIC DSG 0AM (DQ200) 7/1 Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

HYDRAULIC ACTUATION GEARBOX Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

## VOLKSWAGEN (VW) (EU) BEETLE 5C BEETLE 1.6 TDI (77 KW) (2011-2014)



HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 1-1,15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 48 months/ 60000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.