

VOLKSWAGEN (VW) (EU) GOLF II 1G1

GOLF II 1.3 (40 KW) (1985-1988)

**ENGINE MH**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Specialsynth MSP 5W-40****PRODUCT RECOMMENDATION 3****Emperol 5W-40***Change every 15000 km/ 12 months***TRANSAXLE MANUAL 084 4/1**

Capacity: 2,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Check every 15000 km/ 12 months***TRANSAXLE MANUAL 085 5/1**

Capacity: 3,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****PRODUCT RECOMMENDATION 2****SP Gear 5015***Check every 15000 km, change every 12 months***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 15000 km, change every 24 months***COOLING SYSTEM**

Capacity: 6,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11**

VOLKSWAGEN (VW) (EU) GOLF II 1G1

GOLF II 1.3 (40 KW) (1985-1988)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.