

VOLKSWAGEN (VW) (EU) PASSAT CC 357

PASSAT CC 2.0 TDI (100 KW) (2008-2012)



ENGINE CBAA, CFFA
Capacity: 4 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 02Q 6/1
Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1081	SP Gear 5015

Check every 48 months/ 60000 km

TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1
Capacity: 7,2 liter (Initial fill), Capacity: 5,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 2072	

Change every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

Change every 24 months

VOLKSWAGEN (VW) (EU) PASSAT CC 357

PASSAT CC 2.0 TDI (100 KW) (2008-2012)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.