

VOLKSWAGEN (VW) (EU) POLO V 6R/6C

POLO V 1.4 16V (2009-2014)



ENGINE CGGB, CDDA
Capacity: 3,2 liter (Service fill)

USE

Extended drain (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar SP LL-03 0W-30****PRODUCT RECOMMENDATION 2****Helar SP LL-03 5W-30***Change every 30000 km/ 24 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30***Change every 15000 km/ 12 months***TRANSAXLE MANUAL AS OF PRODUCTION DATE 04-12-2013 02T 5/1**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****PRODUCT RECOMMENDATION 2****SP Gear 5015***Check every 24 months/ 30000 km***TRANSAXLE MANUAL UP TO PRODUCTION DATE 04-12-2013 02T 5/1**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****PRODUCT RECOMMENDATION 2****SP Gear 5015***Check every 24 months/ 30000 km***TRANSAXLE SEMI-AUTOMATIC DSG 0AM (DQ200) 7/1**

Capacity: 1,7-1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****PRODUCT RECOMMENDATION 2****SP Gear 5015***Check every 24 months/ 30000 km*

VOLKSWAGEN (VW) (EU) POLO V 6R/6C

POLO V 1.4 16V (2009-2014)



HYDRAULIC ACTUATION GEARBOX

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 1-1,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km/ 24 months, change every 24 months

ELECTRO-HYDRAULIC POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 24 months/ 30000 km

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.