VOLKSWAGEN (VW) (USA / CAN) TIGUAN 5N1 TIGUAN 2.0 TFSI 4MOTION (147 KW)



(2007-2011)

ENGINE BPY, CCTA, CBFA Capacity: 4,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Emperol 5W-40	Asyntho 5W-30		
	·	·	

Change every 10000 miles/ 12 months

BEVEL GEAR / TRANSFERBOX Capacity: 0,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

TRANSAXLE AUTOMATIC 09M 6/1 Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 40000 miles, change every 80000 miles		

TRANSAXLE MANUAL 0A6 6/1 Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 40000 miles/ 24 mont	hs	

KROON-OIL B.V. Postbus 149 7600 AC Almelo PRODUCT RECOMMENDATION

VOLKSWAGEN (VW) (USA / CAN) TIGUAN 5N1 TIGUAN 2.0 TFSI 4MOTION (147 KW)



(2007-2011)

HALDEX-CLUTCH Capacity: 0,85 liter (Initial fill), Capacity: 0,7 liter (Refill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6033		
Change every 36 months		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1,2 liter	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 36 months	
USE	CLIMATE
Subsequently	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

COOLING SYSTEM Capacity: 11 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 40000 miles/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.