

VOLVO (EU) 800 850 2.5 10V B5252FS (1992-1993)



MOTOR B5252FS
Kapacitet: 5,3 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK Aisin Warner 4/1
Kapacitet: 7,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

VOLVO (EU) 800 850 2.5 10V B5252FS (1992-1993)



SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 6 måneder

KØLESYSTEM

Kapacitet: 7,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.