

VOLVO (EU) C70 C70 2.5 T (1998-1999)



MOTOR B5254T

Kapacitet: 5,8 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

PRODUKTANBEFALING 2

Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

PRODUKTANBEFALING 2

Asyntho 5W-30

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK AW50-42 4/1

Kapacitet: 7,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Kontroller alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL M56 5/1

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 15000 km/ 12 måneder

VOLVO (EU) C70 C70 2.5 T (1998-1999)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 12 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING (ATF-HÆTTE)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
ATF Almirol	ATF Dexron II-D	

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.