

VOLVO (EU) S40 S40 1.8 (2000-2004)



MOTOR B4184S2
Kapacitet: 5,4 liter, Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza LSP 5W-30	Helar 0W-40	Emperol 5W-40

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 10000 km/ 6 måneder

TRANSAKSEL AUTOMATISK AW55-50 5/1
Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 4026		

TRANSAKSEL MANUEL M3P 5/1
Kapacitet: 3,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015		

Kontroller alle 20000 km/ 12 måneder

TRANSAKSEL MANUEL M56 5/1
Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015		

Kontroller alle 20000 km/ 12 måneder

VOLVO (EU) S40 S40 1.8 (2000-2004)**HYDRAULISK BREMSE- & KOBLINGSSYSTEM**

Kapacitet: 0,4-0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4*Kontroller alle 20000 km, skift alle 24 måneder***SERVOSTYRING**

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Almirol

PRODUKTANBEFALING 2

ATF Dexron II-D*Kontroller alle 20000 km/ 12 måneder*

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

SP Fluid 3013*Kontroller alle 20000 km/ 12 måneder***KØLESYSTEM**

Kapacitet: 6,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF*Kontroller alle 20000 km/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.