

# VOLVO (EU) S40 S40 D3 (2010-2012)



## MOTOR D5204T5 / D5204T6

Kapacitet: 5,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Presteza MSP 0W-30**

*Skift alle 30000 km/ 12 måneder*

## TRANSAKSEL AUTOMATISK TF-80SD 6/1

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 4036**

## TRANSAKSEL MANUEL M66 6/1

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1081**

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

*Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder*

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

*Skift alle 20000 km/ 12 måneder*

# VOLVO (EU) S40 S40 D3 (2010-2012)



## SERVOSTYRING

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Fluid 3013</b> |  |         |

## KØLESYSTEM

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Coolant SP 18</b> |  |         |

*Kontroller alle 20000 km/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*