

VOLVO (EU) S70 S70 2.3i (1997-1999)



MOTOR B5234S

Kapacitet: 5,8 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1		
HDX 20W-50		

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Bi-Turbo 15W-40		

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK AW50-42 4/1

Kapacitet: 7,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Kontroller alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL M56 5/1

Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 15000 km/ 12 måneder

VOLVO (EU) S70 S70 2.3I (1997-1999)



HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

SERVOSTYRING (ATF-HÆTTE)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
ATF Almirol	ATF Dexron II-D	

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING (CHF HÆTTE)

Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 7,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.