

VOLVO (EU) S80 S80 2.4 (103 KW) (2005-2006)



MOTOR B5244S2

Kapacitet: 5,5-5,8 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza LSP 5W-30

PRODUKTANBEFALING 2

Asyntho 5W-30

Skift alle 30000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Presteza MSP 0W-30

Skift alle 30000 km/ 12 måneder

TRANSAKSEL AUTOMATISK AW55-50 4/1

Kapacitet: 7,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 20000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 20000 km, skift alle 24 måneder

VOLVO (EU) S80 S80 2.4 (103 KW) (2005-2006)



SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.