

VOLVO (EU) S80 S80 T4 (2011-2013)



MOTOR B4204T6
Kapacitet: 5,4 liter (Servicepåfyldning)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Duranza LSP 5W-30

Skift alle 30000 km/ 12 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Presteza MSP 0W-30

Skift alle 30000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK MPS6 (Getrag 6 DCT450) 6/1
Kapacitet: 5,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2072

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL MANUEL MMT6 6/1
Kapacitet: 1,65 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

Skift alle 12 måneder

VOLVO (EU) S80 S80 T4 (2011-2013)



SERVOSTYRING

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 10,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 18

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.