

# VOLVO (EU) V70 V70 2.3i (1997-1999)



## MOTOR B5234S

Kapacitet: 5,8 liter, Filterkapacitet: 0,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3   |
|----------------------|----------------------|-----------------------|
| <b>Emperol 5W-40</b> | <b>Asyntho 5W-30</b> | <b>Emperol 10W-40</b> |

Skift alle 15000 km/ 12 måneder

| ANVEND   | KLIMA            |
|----------|------------------|
| Krævende | Middelhavsagtigt |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>HDX 20W-50</b>   |  |  |

Skift alle 7500 km/ 6 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>Bi-Turbo 15W-40</b> |  |  |

Skift alle 7500 km/ 6 måneder

## TRANSAKSEL AUTOMATISK AW50-42 4/1

Kapacitet: 6,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

Kontroller alle 15000 km/ 12 måneder

## TRANSAKSEL MANUEL M56 5/1

Kapacitet: 2,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>SP Gear 5015</b> |  |  |

Kontroller alle 15000 km/ 12 måneder

# VOLVO (EU) V70 V70 2.3i (1997-1999)



## HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,6 liter

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Skift alle 24 måneder

## SERVOSTYRING

| ANVEND              |                        | KLIMA   |
|---------------------|------------------------|---------|
| Normal              |                        | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2    |         |
| <b>ATF Almirol</b>  | <b>ATF Dexron II-D</b> |         |

Kontroller alle 15000 km/ 12 måneder

## SERVOSTYRING (CHF HÆTTE)

Kapacitet: 0,9 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Fluid 3013</b> |  |         |

Kontroller alle 15000 km/ 12 måneder

## KØLESYSTEM

Kapacitet: 7,2 liter

| ANVEND                        |  | KLIMA   |
|-------------------------------|--|---------|
| Normal                        |  | Moderat |
| PRODUKTANBEFALING 1           |  |         |
| <b>Coolant -38 Organic NF</b> |  |         |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.