

VOLVO (EU) V70 V70 2.5 FT (2008-2009)



MOTOR B5254T8
Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Presteza MSP 0W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK TF-80SC 6/1
Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 7 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 4026

TRANSAKSEL MANUEL M66 6/1
Kapacitet: 2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS
Kapacitet: 0,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 60000 km/ 24 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

Skift alle 30000 km/ 12 måneder

VOLVO (EU) V70 V70 2.5 FT (2008-2009)



SERVOSTYRING

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 18

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.