

VOLVO (EU) XC90 XC90 D5 AWD (2002-2005)



MOTOR D5244T

Kapacitet: 6,5 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 20000 km/ 12 måneder

DIFFERENTIALE BAG (4x4)

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Kontroller alle 20000 km/ 12 måneder

TRANSAKSEL AUTOMATISK AW55-50 AWD 5/1

Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 7 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 20000 km/ 12 måneder

TRANSAKSEL MANUEL M66-AWD 6/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 20000 km/ 12 måneder

VINKELHJUL/TRANSFERGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder

VOLVO (EU) XC90 XC90 D5 AWD (2002-2005)



HALDEX-KOBLING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 6033		

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 20000 km, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 12,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.