

VOLVO (EU) 400 460 1.9 TURBO DIESEL INTERCOOLER (1993-1997)

**ENGINE D19T**

Capacity: 5 liter (Service fill), Filter capacity: 0,75 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Change every 7500 km/ 6 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 km/ 6 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40**TRANSAXLE MANUAL 5/1**

Capacity: 3,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 15000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 30000 km/ 24 months*

VOLVO (EU) 400 460 1.9 TURBO DIESEL INTERCOOLER (1993-1997)



POWER STEERING

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 30000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.