VOLVO (EU) 900 960 3.0 24V B6304F (1991-1996)



| ENGINE B6304F Capacity: 5,75 liter, Capacity: 6,15 liter (D | ry fill), Filter capacity: 0,5 liter | |
|---|--------------------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30 | Emperol 10W-40 | Bi-Turbo 15W-40 |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30 | Emperol 10W-40 | Bi-Turbo 15W-40 |
| Change every 7500 km/ 6 months | | |

| DIFFERENTIAL REAR Capacity: 1,3-1,6 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube GL-5 80W-90 | |
| Check every 15000 km/ 12 months | ' |

| TRANSMISSION AUTOMATIC AW30-43 Capacity: 7,5 liter | 4/1 | |
|---|-----|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Check every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Change every 75000 km | | |
| | | |

VOLVO (EU) 900 960 3.0 24V B6304F (1991-1996)



| TRANSMISSION MANUAL 5/1 Capacity: 2,6 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF-F (Ford) | |

| | CLIMATE |
|--------------------------|----------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Drauliquid-S DOT 4 | |
| | |

Change every 24 months

| POWER STEERING Capacity: 0,8 liter | | | |
|---------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| ATF-A | ATF-F (Ford) | | |
| Check every 15000 km/ 12 months | . change every 24 months | | |

| COOLING SYSTEM Capacity: 8,5 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.