SP Matic 4036

VOLVO (EU) C70 C70 D3 (2010-2013)



ENGINE D5204T5 / D5204T6 Capacity: 5,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-30	
Change every 30000 km/ 12 months	

TRANSAXLE AUTOMATIC TF-80SC 6/1
Capacity: 7 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

TRANSAXLE MANUAL M66 6/1
Capacity: 1,9 liter

USE

Normal

PRODUCT RECOMMENDATION 1

SP Gear 1081

CLIMATE

Moderate

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 20000 km, change every 40000 km/24 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 20000 km/ 12 months	

VOLVO (EU) C70 C70 D3 (2010-2013)



POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 8,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 18	
Chook ayon, 20000 km/ 12 months	·

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.