VOLVO (EU) S40 S40 1.8I (DIRECT INJ.) (1998-2000)



| ENGINE B4184SM Capacity: 3,8 liter, Filter capacity: 0,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 5W-40 | Asyntho 5W-30 | Emperol 10W-40 |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 15W-40 | | |
| Change every 7500 km/ 6 months | | |

 TRANSAXLE MANUAL M5M42 5/1

 Capacity: 2,2 liter

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 Moderate

 SP Gear 5015
 Change every 105000 km

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4-0,5 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| 04 | |

Change every 24 months

VOLVO (EU) S40 S40 1.8I (DIRECT INJ.) (1998-2000)



| POWER STEERING Capacity: 1 liter | | |
|-------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| ATF Almirol | ATF Dexron II-D | |
| Check every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |
| Check every 15000 km/ 12 months | | |
| | | |

| COOLING SYSTEM Capacity: 6 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.