VOLVO (EU) S60 S60 T5 (187 KW) (2012-2013)



| ENGINE B5254T12 Capacity: 5,5 liter (Service fill) | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Presteza MSP 0W-30 | |
| Change every 30000 km/ 12 months | |
| | |

| TRANSAXLE AUTOMATIC TF-80SC 6/ Capacity: 7 liter | 1 | |
|---|---|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Check every 12 months/ 30000 km | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| Change every 12 months | · |

| POWER STEERING Capacity: 1,2 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |
| Check every 12 months/ 30000 km | · |

| COOLING SYSTEM Capacity: 8,9 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 18 | |
| Check every 12 months/ 30000 km | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

VOLVO (EU) S60 S60 T5 (187 KW) (2012-2013)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.