## **VOLVO (EU) S80 S80 3.2** (2006-2007)



ENGINE B6324S Capacity: 7,7 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Presteza MSP 0W-30	

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC TF-80SC 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
USE	CLIMATE		
Severe	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Change every 60000 km/ 24 months			

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 30000 km/ 12 months, change every 60000 km/	24 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 30000 km/ 12 months	

Change every 30000 km/ 12 months

## VOLVO (EU) S80 S80 3.2 (2006-2007)



POWER STEERING Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Chack ayany 12 months/ 20000 km	

Check every 12 months/ 30000 km

COOLING SYSTEM Capacity: 8,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 12 months/ 30000 km	·

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.