

VOLVO (EU) V90 V90 2.5 24V B6254F (1996-1998)**ENGINE B6254F**

Capacity: 5,75 liter, Capacity: 6,15 liter (Dry fill), Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Change every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

*Change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Check every 15000 km/ 12 months***TRANSMISSION AUTOMATIC Aisin Warner 4/1**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Check every 15000 km/ 12 months***TRANSMISSION MANUAL M90 5/1**

Capacity: 1,75 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 15000 km/ 12 months

VOLVO (EU) V90 V90 2.5 24V B6254F (1996-1998)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 24 months***POWER STEERING**

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF-A	ATF-F (Ford)	

*Check every 15000 km/ 12 months***COOLING SYSTEM**

Capacity: 10,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.