VOLVO (EU) XC60 XC60 2.4D (120 KW) AWD (2010-2011)



ENGINE D5244T16 Capacity: 5,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-30	
01	

Change every 30000 km/ 12 months

BEVEL GEAR TRANSFERBOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

T KODOOT KEOOMMENDATION 2	
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Moderate
	CLIMATE

TRANSAXLE AUTOMATIC TF-80SC/SDAWD 6/1 Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

TRANSAXLE MANUAL M66-AWD 6/1

VOLVO (EU) XC60 XC60 2.4D (120 KW) AWD (2010-2011)



USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
HALDEX-CLUTCH	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 6033	
HYDRAULIC BRAKE/CLUTCH SYSTE	EM ABS
Capacity: 0,6 liter	0.111.75
use	CLIMATE
	Moderate
USE	
use Normal	

CLIMATE
Moderate

Check every 12 months/ 30000 km

COOLING SYSTEM Capacity: 11 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 18	
Check every 12 months/ 30000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.