

# FAW MEDIUM AND HEAVY TRUCKS

## CA1083P9 4X2 (EURO 2)

**ENGINE** CA4DF3-13E3

Capacity: 15-18 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 10000 km/ 12 months***DIFFERENTIAL REAR**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Change every 10000 km/ 12 months***TRANSMISSION** FAW CA5T 5/1

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140***Change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 10000 km/ 12 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 12 months*

# FAW MEDIUM AND HEAVY TRUCKS

## CA1083P9 4X2 (EURO 2)

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*