HIGER A98 A90 KLQ6147S (2009 AND AFTER)



ENGINE DT12	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Dieselfleet CD+ 15W-40	

DIFFERENTIAL REAR Scania		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	
PROPUGT PEROMMENDATION 4	
Normal Moderate Moderate	

HYDRAULIC DAMPER Opticruise Capacity: 90 CM3		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HIGER A98 A90 KLQ6147S (2009 AND AFTER)



HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Coolant -26		
		PRODUCT RECOMMENDATION 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.