AHLMANN FRONT LOADERS AF AF 1200 CUMMINS B3.3TAA (2010-2015)



ENGINE Cummins B3.3TAA Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40
Check every 10 hours, change every 50	0 hours	·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40
Check every 10 hours, change every 50	hours	

DIFFERENTIAL FRONT LIMITED SLIP Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 50 hours, change every 1s	00 hours
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 50 hours, change every 50	0 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 50 hours, change every 1500 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

PRODUCT RECOMMENDATION 1

AHLMANN FRONT LOADERS AF AF 1200 CUMMINS B3.3TAA (2010-2015)



HUB REDUCTIONS FRONT Capacity: 0,8 liter (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 1500	hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 500 h	nours	
HUB REDUCTIONS REAR Capacity: 0,8 liter (each side)		
USE		CLIMATE
Normal		Moderate

Gearlube LS 80W-90	
Check every 50 hours, change every 1500 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 50 hours, change every 500 hours	

TRANSFERBOX Capacity: 1,25 liter (20 km/h version), Capacity: 4 liter (30 km/h version)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 1500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 500 hours		

AHLMANN FRONT LOADERS AF AF 1200 CUMMINS B3.3TAA (2010-2015)



HYDRAULIC SYSTEM Capacity: 80 liter (Hydraulic tank), Capacity: 134 liter (Total)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 10 hours, change every 1500 hours		

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 10 hours		

COOLING SYSTEM Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Charles and FO because about a sur	45001	

Check every 50 hours, change every 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.