AHLMANN SWING LOADERS AS AS 150 DEUTZ BF4M2012C (2001-2008)



ENGINE Deutz BF4M-2012C Capacity: 10 liter			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Agrisynth LSP 10W-40			
Change every 100 hours			
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, am	pient temperature > -10°C	Moderate	
PRODUCT RECOMMENDATION 1			
Agrisynth LSP 10W-40			
Check every 10 hours, change every 500	hours/ 12 months		

DIFFERENTIAL FRONT Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 750 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 100 hours	

Capacity: 12,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 750 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Gearlube LS 80W-90 Change every 100 hours	

DIFFERENTIAL REAR

AHLMANN SWING LOADERS AS AS 150 DEUTZ BF4M2012C (2001-2008)



HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 750 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 100 hours	
HUB REDUCTIONS REAR Capacity: 1,9 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 750 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 100 hours	
TRANSFERBOX Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 1500 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 100 hours	

AHLMANN SWING LOADERS AS AS 150 DEUTZ BF4M2012C (2001-2008)



HYDRAULIC SYSTEM Capacity: 160 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours	
USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
Change every 1500 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.