PRODUCT RECOMMENDATION

AICHI WHEELED BOOMLIFTS SP/ISP SP18A ISUZU A-4JB1 (2001 AND AFTER)

ENGINE Isuzu 4JB1
Capacity: 6,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP Ultra FE 5W-30	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP Ultra FE 5W-30	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 150 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 1200 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 100 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AICHI WHEELED BOOMLIFTS SP/ISP SP18A ISUZU A-4JB1 (2001 AND AFTER)

COOLING SYSTEM
Capacity: 5 liter (Engine only)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

SWING REDUCTION GEARBOX
Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 1200 hours/ 12 months		
USE		**CLIMATE**
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 3 months/ 300 hours		

TRAVEL REDUCTION GEARBOX
Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 1200 hours/ 12 months		
USE		**CLIMATE**
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 3 months/ 300 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367