

# AICHI AERIAL PLATFOM, SCISSOR TYPE

## RV RV123 ISUZU 4JB1 (1997-2008)



**ENGINE** Isuzu 4JB1  
Capacity: 6,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Change every 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 250 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

*Change every 1200 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

*Change every 1200 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

*Change every 1 months/ 100 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

*Change every 1 months/ 100 hours*

# AICHI AERIAL PLATFORM, SCISSOR TYPE

## RV RV123 ISUZU 4JB1 (1997-2008)



### GREASE POINTS/NIPPLES ANCHOR PINS FOR LIFT CYLINDER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 30 hours*

### GREASE POINTS/NIPPLES GUIDE RAIL AND ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 30 hours*

### GREASE POINTS/NIPPLES PIVOT PINS FOR SCISSOR ARMS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 30 hours*

### TRAVEL REDUCTION GEARBOX

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1200 hours/ 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1 months/ 100 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.