PRODUCT RECOMMENDATION

# AMMANN SINGLE DRUM ROLLERS ASC ASC 110 D CUMMINS TIER 2

**ENGINE** Cummins QSB5.9-C155
Capacity: 16,3 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** | **Synfleet SHPD 10W-40** |

*Check every 20 hours, change every 3 months/ 250 hours*

**TRANSMISSION DRUM DRIVE**
Capacity: 4,2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube HS GL-5 80W-140** | | |

*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube HS GL-5 80W-140** | | |

*Change every 100 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 100 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AMMANN SINGLE DRUM ROLLERS ASC ASC 110 D CUMMINS TIER 2

## WHEEL GEARS
Capacity: 2,8 liter (each)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube HS GL-5 80W-140** | | |
| *Check every 3 months/ 250 hours, change every 12 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |
| *Check every 3 months/ 250 hours, change every 12 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube HS GL-5 80W-140** | | |
| *Change every 100 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 100 hours* | | |

## HYDRAULIC SYSTEM
Capacity: 90 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Perlus H 46** | **Perlus H 68** | |
| *Check every 20 hours, change every 24 months/ 2000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| **Perlus H 32** | | |
| *Check every 20 hours, change every 24 months/ 2000 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AMMANN SINGLE DRUM ROLLERS ASC ASC 110 D CUMMINS TIER 2

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **HT Q9 High Grade Grease** | **Labora Grease** | **Q5 MP Calcep Grease EP 2** |

*Change every 250 hours/ 3 months*

## COOLING SYSTEM
Capacity: 25 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 20 hours, change every 24 months/ 2000 hours*

## VIBRATORY DRUM FRONT
Capacity: 8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** | **Synfleet SHPD 10W-40** |

*Check every 250 hours/ 3 months, change every 24 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367