

AMMANN ARTICULATED TANDEM ROLLERS AV AV 70 X CUMMINS TIER 3



ENGINE Cummins B3.3-C80
Capacity: 7 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
---	--	--

Check every 20 hours, change every 3 months/ 250 hours

TRANSMISSION DRUM DRIVE
Capacity: 1,4 liter

USE Normal		CLIMATE Tropical
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube HS GL-5 80W-140		
--	--	--

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE Normal		CLIMATE Mediterranean
----------------------	--	---------------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM
Capacity: 40 liter

USE Normal		CLIMATE Mediterranean
----------------------	--	---------------------------------

PRODUCT RECOMMENDATION 1 Perlus H 46	PRODUCT RECOMMENDATION 2 Perlus H 68	
---	---	--

Check every 20 hours, change every 24 months/ 2000 hours

USE Normal		CLIMATE Arctic
----------------------	--	--------------------------

PRODUCT RECOMMENDATION 1 Perlus H 32		
---	--	--

Check every 20 hours, change every 24 months/ 2000 hours

AMMANN ARTICULATED TANDEM ROLLERS AV AV 70 X CUMMINS TIER 3



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

Change every 250 hours/ 3 months

COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20 hours, change every 24 months/ 2000 hours

VIBRATORY DRUM

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Check every 250 hours/ 3 months, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.