ARTISON FORKLIFT TRUCKS, DIESEL FD15



ENGINE Isuzu C240PKF-23		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	HDX 40	
Check every 8 hours, change every 200 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		
Check every 8 hours, change every 200 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
HDX 10W		
Check every 8 hours, change every 200 hours		

TRANSMISSION Powershift Capacity: 7,6 liter, Capacity: 8-9 liter	r (Dry fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	Unigear LS GL-3/GL-5 85W-140
Charles and 200 hours above our		

Check every 200 hours, change every 1000 hours

HYDRAULIC SYSTEM Capacity: 45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus AF 46		
Check every 8 hours, change every 2000 hours		

ARTISON FORKLIFT TRUCKS, DIESEL FD15



HYDRAULIC BRAKE SYSTEM Capacity: 0,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Check every 200 hours	·

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Check every 200 hours	'

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 8 hours	<u> </u>	<u> </u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.