PRODUCT RECOMMENDATION

ARTISON FORKLIFT TRUCKS, DIESEL FD25

ENGINE Isuzu 4JG2		
USE Normal		**CLIMATE** Tropical
PRODUCT RECOMMENDATION 1 **Multifleet SCD 40**	**PRODUCT RECOMMENDATION 2** **HDX 40**	
Check every 8 hours, change every 200 hours		
USE Normal		**CLIMATE** Mediterranean
PRODUCT RECOMMENDATION 1 **HDX 30**		
Check every 8 hours, change every 200 hours		
USE Normal		**CLIMATE** Cold
PRODUCT RECOMMENDATION 1 **HDX 10W**		
Check every 8 hours, change every 200 hours		

ENGINE Isuzu C240PKF-23		
USE Normal		**CLIMATE** Tropical
PRODUCT RECOMMENDATION 1 **Multifleet SCD 40**	**PRODUCT RECOMMENDATION 2** **HDX 40**	
Check every 8 hours, change every 200 hours		
USE Normal		**CLIMATE** Mediterranean
PRODUCT RECOMMENDATION 1 **HDX 30**		
Check every 8 hours, change every 200 hours		
USE Normal		**CLIMATE** Cold
PRODUCT RECOMMENDATION 1 **HDX 10W**		
Check every 8 hours, change every 200 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ARTISON FORKLIFT TRUCKS, DIESEL FD25

TRANSMISSION Powershift
Capacity: 7,6 liter, Capacity: 8-9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	**Unigear LS GL-3/GL-5 85W-140**

Check every 200 hours, change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus AF 46		

Check every 8 hours, change every 2000 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Check every 200 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 200 hours

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 8 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367