

ARTISON FORKLIFT TRUCKS, DIESEL FD50

**ENGINE** Perkins 1004-42

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Multifleet SCD 40 | HDX 40 | |

Check every 8 hours, change every 200 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| HDX 30 | | |

Check every 8 hours, change every 200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| HDX 10W | | |

Check every 8 hours, change every 200 hours

TRANSMISSION Powershift
 Capacity: 7,6 liter, Capacity: 8-9 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|------------------------------------|-------------------------------------|
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Unigear LS GL-3/GL-5 85W-140 |

Check every 200 hours, change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 45 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus AF 46 | | |

Check every 8 hours, change every 2000 hours

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Check every 200 hours***GREASE POINTS/NIPPLES**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 200 hours***COOLING SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 8 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.