

# ASV TRACKED LOADERS PT-60 (2008 AND AFTER)



**ENGINE** Perkins 404D-22T  
Capacity: 10,6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 6 months/ 250 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Check every 10 hours, change every 6 months/ 250 hours*

**HYDRAULIC SYSTEM**  
Capacity: 30,3 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 32</b>	

*Check every 10 hours, change every 500 hours*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 10 hours*

**COOLING SYSTEM**  
Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*