

# ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET ET-18L (2005 AND AFTER)



## DIFFERENTIAL FRONT

| USE                                       |                          | CLIMATE  |
|---|--------------------------|----------|
| Normal                                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b>                  | <b>Agrifluid HT</b>      |          |
| <i>Change every 12 months/ 2400 hours</i> |                          |          |

## REDUCTION GEARS

| USE                                       |  | CLIMATE       |
|---|--|---------------|
| Normal                                    |  | Mediterranean |
| PRODUCT RECOMMENDATION 1                  |  |               |
| <b>Unigear LS GL-3/GL-5 85W-140</b>       |  |               |
| <i>Change every 12 months/ 2400 hours</i> |  |               |

| USE                                       |                          | CLIMATE                  |
|---|--------------------------|--------------------------|
| Normal                                    |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b>                  | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |
| <i>Change every 12 months/ 2400 hours</i> |                          |                          |

## HYDRAULIC SYSTEM

| USE                                      |  | CLIMATE  |
|--|--|----------|
| Normal                                   |  | Moderate |
| PRODUCT RECOMMENDATION 1                 |  |          |
| <b>Perlus H 32</b>                       |  |          |
| <i>Change every 6 months/ 1200 hours</i> |  |          |

| USE                                      |  | CLIMATE |
|--|--|---------|
| Normal                                   |  | Arctic  |
| PRODUCT RECOMMENDATION 1                 |  |         |
| <b>Perlus H 15</b>                       |  |         |
| <i>Change every 6 months/ 1200 hours</i> |  |         |

## HYDRAULIC BRAKE SYSTEM

| USE                                       |                           | CLIMATE  |
|---|---------------------------|----------|
| Normal                                    |                           | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b>          | <b>Drauliquid-S DOT 4</b> |          |
| <i>Change every 12 months/ 2400 hours</i> |                           |          |

# ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET ET-18L (2005 AND AFTER)



## GREASE POINTS/NIPPLES

| USE                                     |  | CLIMATE  |
|---|--|----------|
| Normal                                  |  | Moderate |
| PRODUCT RECOMMENDATION 1                |  |          |
| <b>Gear Grease EP 1</b>                 |  |          |
| <i>Change every 3 months/ 600 hours</i> |  |          |

## GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE                                       |                                 | CLIMATE                      |
|---|---------------------------------|------------------------------|
| Normal                                    |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>                      | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |
| <i>Change every 12 months/ 2400 hours</i> |                                 |                              |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.