

# AUSA FORKLIFT TRUCKS CH 150 ISUZU 3LD1 (2000-2005)

**ENGINE** Isuzu 3LD1

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 250 hours/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Change every 250 hours/ 6 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Change every 50 hours***DIFFERENTIAL REAR HUB REDUCTIONS (4x4)**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 50 hours*

# AUSA FORKLIFT TRUCKS CH 150 ISUZU 3LD1 (2000-2005)



## POWER TAKE OFF 4x4

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

## REDUCTOR UNIT

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 1000 hours*

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 50 hours*

## HYDRAULIC SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 46</b>       |  |          |

*Change every 1000 hours*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Initial service          |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 46</b>       |  |          |

*Change every 50 hours*

# AUSA FORKLIFT TRUCKS CH 150 ISUZU 3LD1 (2000-2005)



## ARTICULATION JOINTS

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Multifleet SCD 30</b> |  |               |

*Change every 50 hours*

| USE                         |                             | CLIMATE                       |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 50 hours*

## GREASE POINTS/NIPPLES

| USE                      |                          | CLIMATE                         |
|--------------------------|--------------------------|---------------------------------|
| Normal                   |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>Labora Grease</b>     | <b>MoS2 Grease EP 2</b>  | <b>Q5 MP Calcep Grease EP 2</b> |

*Change every 50 hours*

## GREASE POINTS/NIPPLES MAST CHAINS

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 50 hours*

## GREASE POINTS/NIPPLES MAST GUIDES

| USE                      |                          | CLIMATE                         |
|--------------------------|--------------------------|---------------------------------|
| Normal                   |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>Labora Grease</b>     | <b>MoS2 Grease EP 2</b>  | <b>Q5 MP Calcep Grease EP 2</b> |

*Change every 50 hours*

# AUSA FORKLIFT TRUCKS CH 150 ISUZU 3LD1 (2000-2005)

**COOLING SYSTEM**

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Change every 750 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*