
## **AUSA WHEELED DUMPERS 400 AH ISUZU**

(1996-2005)



| USE   |                          | CLIMATE                  |
|---|--------------------------|--------------------------|
| Normal                                      |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40                      | Multifleet SHPD 15W-40   | Multifleet SCD 30        |
| Change every 200 hours                      |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
| Multifleet SCD 20W-20                       |                          |                          |
| Change every 200 hours                      |                          |                          |
| USE   |                          | CLIMATE                  |
| Initial service                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40                      | Multifleet SHPD 15W-40   | Multifleet SCD 30        |
| Change every 50 hours                       |                          |                          |
| USE   |                          | CLIMATE                  |
| Initial service                             |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
| Multifleet SCD 20W-20                       |                          |                          |
| Change every 50 hours                       |                          |                          |
|   |                          |                          |
| <b>DIFFERENTIAL FRONT</b> Capacity: 2 liter |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal                                      |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
| Gearlube LS 80W-90                          |                          |                          |
| Change every 1000 hours                     |                          | I                        |
| USE   |                          | CLIMATE                  |
| Initial service                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                    |                          |                          |
|   | · ·                      | I .                      |

## **AUSA WHEELED DUMPERS 400 AH ISUZU**





| DIFFERENTIAL DEAD                                    |             |
|--|-------------|
| <b>DIFFERENTIAL REAR</b> Capacity: 2,25 liter        |             |
| USE  | CLIMATE     |
| Normal   | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Gearlube LS 80W-90                                   |             |
| Change every 1000 hours                              |             |
| USE  | CLIMATE     |
| Initial service                                      | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Gearlube LS 80W-90                                   |             |
| Change every 50 hours                                |             |
|  |             |
| HUB REDUCTIONS Capacity: 0,25 liter (each hub)       |             |
| USE  | CLIMATE     |
| Normal   | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Gearlube LS 80W-90                                   |             |
| Change every 1000 hours                              |             |
| USE  | CLIMATE     |
| Initial service                                      | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Gearlube LS 80W-90                                   |             |
| Change every 50 hours                                |             |
|  |             |
| HYDRAULIC SYSTEM Capacity: 50 liter (Hydraulic tank) |             |
| USE  | CLIMATE     |
| Normal   | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Perlus H 46  |             |
| Change every 1000 hours                              |             |
| USE  | <br>CLIMATE |
| Initial service                                      | Moderate    |
| PRODUCT RECOMMENDATION 1                             |             |
| Perlus H 46  |             |

Change every 100 hours

## **AUSA WHEELED DUMPERS 400 AH ISUZU**

(1996-2005)



| HYDRAULIC ACTUATION OIL IMMERSED BRAKES |                          |          |  |  |
|---|--------------------------|----------|--|--|
| USE                                     |                          | CLIMATE  |  |  |
| Normal                                  |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2 |          |  |  |
| Multifleet SCD 10W                      | HDX 10W                  |          |  |  |
| Change every 1000 hours                 |                          |          |  |  |

## **ARTICULATION JOINTS**

We are unable to give a standard recommendation for this component. Please contact our service department.

| GREASE POINTS/NIPPLES    |                          |                          |  |  |
|--------------------------|--------------------------|--------------------------|--|--|
| USE                      |                          | CLIMATE                  |  |  |
| Normal                   |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |  |  |
| Change every 50 hours    | -                        | '                        |  |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.