

AUSA WHEELED DUMPERS D 175 RMS 4X2

KUBOTA D902 (2008 AND AFTER)



ENGINE Kubota D902
Capacity: 3,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Change every 100 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 100 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 50 hours

DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 40 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

AUSA WHEELED DUMPERS D 175 RMS 4X2

KUBOTA D902 (2008 AND AFTER)



TRANSMISSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 40 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 46	Perlus AF 46

Check every 40 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 46	Perlus AF 46

Change every 50 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 40 hours, change every 1000 hours

CABLES AND ARTICULATIONS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

AUSA WHEELED DUMPERS D 175 RMS 4X2

KUBOTA D902 (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 3,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 3****Coolant -26**

Check every 40 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.