

AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-28 6X6


ENGINE Cummins LT10-250

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet LSP Ultra 10W-30

DIFFERENTIAL LIMITED SLIP AXLE 1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 800 hours/ 12 months

DIFFERENTIAL LIMITED SLIP AXLE 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 800 hours/ 12 months

DIFFERENTIAL LIMITED SLIP AXLE 3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 800 hours/ 12 months

HUB REDUCTIONS AXLE 1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 800 hours/ 12 months

AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-28 6X6



HUB REDUCTIONS AXLE 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 800 hours/ 12 months</i>		

HUB REDUCTIONS AXLE 3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 800 hours/ 12 months</i>		

TRANSMISSION ZF 6WG200

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
<i>Change every 1200 hours/ 12 months</i>		

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

AVELING BARFORD ARTICULATED DUMP TRUCKS RXD-28 6X6



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.