

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK 6.3 (6X6) MERCEDES-BENZ OM501LA (STAGE



ENGINE Mercedes-Benz OM501LA
Capacity: 32 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|----------------------------|--|
| Agrisynth LSP 10W-40 | Armado Synth 10W-40 | |

Change every 500 hours

DIFFERENTIAL FRONT (WET DISC BRAKES) 25A6HA
Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|----------------------------------|--|--|
| Agrifluid Synth XHP Ultra | | |

Change every 1500 hours

DIFFERENTIAL FRONT (WET DISC BRAKES) Meritor 25M6HA

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 2000 hours

DIFFERENTIAL MIDDLE (WET DISC BRAKES) 25A6HB
Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|----------------------------------|--|--|
| Agrifluid Synth XHP Ultra | | |

Change every 1500 hours

DIFFERENTIAL MIDDLE (WET DISC BRAKES) Meritor 25M6HB

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 2000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK 6.3 (6X6) MERCEDES-BENZ OM501LA (STAGE



DIFFERENTIAL REAR (WET DISC BRAKES) 25U6HA

Capacity: 47 liter (Dry fill), Capacity: 46 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra*Change every 1500 hours*

DIFFERENTIAL REAR (WET DISC BRAKES) Meritor 25U6HA

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Agrifluid HT*Change every 2000 hours*

FINAL DRIVES

Capacity: 4 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 500 hours, change every 1000 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours*

TRANSFERBOX VGR 17000

Capacity: 4,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours*

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B40D MK 6.3 (6X6) MERCEDES-BENZ OM501LA (STAGE

**TRANSMISSION** Allison 4500R ORS 6/1

Capacity: 40 liter (Dry fill), Capacity: 34 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours***TRANSMISSION** ZF 6HP592C 6/1

Capacity: 30 liter (Dry fill), Capacity: 10-15 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 185 liter (Hydraulic system including tank), Capacity: 177,6 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Change every 3000 hours***GREASE POINTS/NIPPLES**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2**COOLING SYSTEM**

Capacity: 33,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.