

# BELL EQUIPMENT RIGID TRACTORS & HAULERS 1226A MKIII JOHN DEERE 6068TF150



**ENGINE** John Deere 6068 TF150  
Capacity: 19 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
|------------------------------|-------------------------------|-----------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> |

*Change every 250 hours/ 6 months*

**DIFFERENTIAL REAR**  
Capacity: 32 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Check every 250 hours, change every 1000 hours*

**TRANSMISSION** Allison 2500 TC211 5/1  
Capacity: 16,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 2032</b>     |  |  |

*Check every 250 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 147 liter (Hydraulic system including tank)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |  |

*Check every 250 hours, change every 3000 hours*

## GREASE POINTS/NIPPLES WHEEL BEARINGS + DRIVE TRAIN

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# BELL EQUIPMENT RIGID TRACTORS & HAULERS 1226A MKIII JOHN DEERE 6068TF150

**COOLING SYSTEM**

Capacity: 19 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 24 months/ 3000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*