

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A MKIII JOHN DEERE 6068TF250



ENGINE John Deere 6068 TF250
Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

Change every 250 hours/ 6 months

DIFFERENTIAL REAR
Capacity: 32 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 1000 hours

TRANSMISSION Allison 3000 TC415 6/1
Capacity: 26,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 250 hours, change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 147 liter (Hydraulic system including tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	Perlus AF 68	

Check every 250 hours, change every 3000 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS + DRIVE TRAIN

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A MKIII JOHN DEERE 6068TF250

**COOLING SYSTEM**

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.