BOBCAT EXCAVATORS E10 KUBOTA D722-E2B (TIER 2) (A33P11001->) (2010-2019)



ENGINE Kubota D722-E2B		
Capacity: 3,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	
Check every 10 hours, change ever	y 500 hours/ 12 months	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change ever	y 500 hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change ever	y 500 hours/ 12 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
	y 500 hours/ 12 months	
Multifleet SCD 10W	y 500 hours/ 12 months	CLIMATE
Multifleet SCD 10W Check every 10 hours, change ever	y 500 hours/ 12 months	сымате Tropical
Multifleet SCD 10W Check every 10 hours, change every	y 500 hours/ 12 months PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W Check every 10 hours, change every use Initial service		
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours	PRODUCT RECOMMENDATION 2	Tropical
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours	PRODUCT RECOMMENDATION 2	ССІМАТЕ
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours USE Initial service	PRODUCT RECOMMENDATION 2	ССІМАТЕ
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	ССІМАТЕ
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30	PRODUCT RECOMMENDATION 2	ССІМАТЕ
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours	PRODUCT RECOMMENDATION 2	Tropical CLIMATE Mediterranean
Multifleet SCD 10W Check every 10 hours, change every use Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours	PRODUCT RECOMMENDATION 2	CLIMATE Mediterranean CLIMATE

BOBCAT EXCAVATORS E10 KUBOTA D722-E2B (TIER 2) (A33P11001->) (2010-2019)



USE	CLIMATE	
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours		

TRAVEL REDUCTION UNIT SEPARATE I Capacity: 0,5 liter (each)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30	
Check every 250 hours, change every 1000	0 hours/ 12 months		

HYDRAULIC SYSTEM Capacity: 10,1 liter (Complete), Capacity: 2,6 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 1000 hours/ 12 months

COOLING SYSTEM Capacity: 3 liter		
use Normal	climate Moderate	
PRODUCT RECOMMENDATION 1	iviouerate	
Coolant -33 MPG		

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.