BOMAG PAVERS BF BF 300 P KUBOTA V3307-DI-T3



| ENGINE Kubota V3307-DI-TE3 Capacity: 11,2 liter | | |
|-----------------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Check every 10 hours, change every 500 l | hours | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |
| Check every 10 hours, change every 500 l | hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |
| Check every 10 hours, change every 500 l | hours | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Check every 10 hours, change every 500 l | hours | |
| USE | | CLIMATE |
| Initial service | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |
| Change every 50 hours | | |

BOMAG PAVERS BF BF 300 P KUBOTA V3307-DI-T3



| USE | CLIMATE |
|--------------------------|---------|
| Initial service | Arctic |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |
| Change every 50 hours | |

| DIFFERENTIAL REAR Capacity: 20 liter | |
|-----------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube HS GL-5 80W-140 | |

| HUB REDUCTIONS REAR Capacity: 8 liter (each hub) | |
|-----------------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube HS GL-5 80W-140 | |

| HYDRAULIC SYSTEM Capacity: 80 liter | | | |
|----------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus Biosynth 46 | Perlus H 46 | | |

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |

BOMAG PAVERS BF BF 300 P KUBOTA V3307-DI-T3



| COOLING SYSTEM Capacity: 14 liter | |
|--------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| | |

Check every 10 hours, change every 24 months

| AUGER DRIVE CHAIN BOX | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HT Q9 High Grade Grease | Labora Grease | |

| BEARING FOR FAN BRACKET | | | |
|--------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| HT Q9 High Grade Grease | Labora Grease | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.