PRODUCT RECOMMENDATION

BOMAG COMBINATION ROLLERS BW-AC/SC BW-120AC-3 DEUTZ F2L 1011 (1995-2004)

ENGINE Deutz F2L-1011
Capacity: 6,5 liter

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Kroontrak CVT 10W-40**	**Agrisynth MSP 10W-40**

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 2000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BOMAG COMBINATION ROLLERS BW-AC/SC BW-120AC-3 DEUTZ F2L 1011 (1995-2004)

ARTICULATED JOINT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367