BOMAG COMBINATION ROLLERS BW-AC/SC BW-90AC-2 KUBOTA D722B (1995-2011)



ENGINE Kubota D722 Capacity: 3,9 liter CLIMATE Normal, fuel sulfur level <0,5 % Tropical PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Check every 10 hours, change every 250 hours/ 12 months CLIMATE Normal, fuel sulfur level <0,5 % Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 250 hours/ 12 months CLIMATE Normal, fuel sulfur level <0,5 % Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30 Synfleet SHPD 10W-40 Multifleet SHPD 10W-40 Check every 10 hours, change every 250 hours/ 12 months CLIMATE Normal, fuel sulfur level <0,5 % Arctic PRODUCT RECOMMENDATION 1 Multifleet SCD 10W Check every 10 hours, change every 250 hours/ 12 months CLIMATE Initial service **Tropical** PRODUCT RECOMMENDATION 1 **Multifleet SCD 30** Change every 50 hours USE CLIMATE Initial service Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE CLIMATE Initial service Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30 Synfleet SHPD 10W-40 **Multifleet SHPD 10W-40**

Change every 50 hours

PRODUCT RECOMMENDATION

BOMAG COMBINATION ROLLERS BW-AC/SC BW-90AC-2 KUBOTA D722B (1995-2011)



USE CLIMATE
Initial service Arctic

PRODUCT RECOMMENDATION 1
Multifleet SCD 10W

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 32	Perlus AF 32		
Check every 10 hours, change every 2000 hours/24 months			

COOLING SYSTEM Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ry 2000 hours/ 24 months	

ARTICULATED JOINT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.