

BOMAG LANDFILL COMPACTORS BC BC-572RB DEUTZ BF6M-1013FC (TIER 2) S/N 10157063 -> (2002-2006)



ENGINE Deutz BF6M-1013FC
Capacity: 17,5 liter, Filter capacity: 1,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Armado Synth 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth 5W-30

Check every 10 hours, change every 250 hours/ 12 months

PLANETARY GEARS
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 350 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

Check every 10 hours, change every 2000 hours/ 24 months

CENTRAL LUBRICATION SYSTEM
Capacity: 2 kg

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

COOLING SYSTEM
Capacity: 36 liter

USE
Normal, fuel sulfur level <0,5 %

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2
Coolant -26

Check every 10 hours, change every 24 months

PRODUCT RECOMMENDATION

BOMAG LANDFILL COMPACTORS BC BC-572RB DEUTZ BF6M-1013FC (TIER 2) S/N 10157063 -> (2002-2006)



SPLITTER GEARBOX

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.