

BOMAG TANDEM VIBRATORY ROLLERS

BW-AD/SL BW-125ADH DEUTZ F3L 2011

(S/N 101 17021 1210...>)(2004-2006)



ENGINE Deutz F3L-2011
Capacity: 6 liter

USE

Normal, continuous ambient temperature > -10°C and sulfur content in fuel < 0,5 %

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 10 hours, change every 1000 hours/ 12 months

USE

Normal, continuous ambient temperature > -10°C and sulfur content in fuel < 0,5 %

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 1000 hours/ 12 months

USE

Normal, continuous ambient temperature > -10°C and sulfur content in fuel < 0,5 %

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Check every 10 hours, change every 1000 hours/ 12 months

USE

Normal, continuous ambient temperature > -10°C and sulfur content in fuel < 0,5 %

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

Check every 10 hours, change every 1000 hours/ 12 months

USE

Normal, continuous ambient temperature > -10°C and sulfur content in fuel < 0,5 %

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 30 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

Check every 10 hours, change every 2000 hours/ 24 months

BOMAG TANDEM VIBRATORY ROLLERS

BW-AD/SL BW-125ADH DEUTZ F3L 2011

(S/N 101 17021 1210...>)(2004-2006)



ARTICULATED JOINT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.